

NETWORK CAMERA

NCM-001 (SK-N140X)



● FEATURES

- MPEG4 dual stream
- Built-in web server
- DDNS support
- High Quality Images (up to 30fps@704x480)
- 1/3" COLOR SONY EXview HAD CCD
- 50M Range visible in total darkness with 40pcs of IR LEDs
- True Daynight function(Exchange of two installation)
- Weather-proof for outdoor use
- Extra video test connector for easy installation
- Cable through bracket
- All-in-one(Built-in Lens, IR LEDs, Sun-visor & Bracket)

● SPECIFICATION

MODEL	NCM-001 (SK-N140X)
NETWORK	RJ-45, 10/100BASE-T Ethernet
Static IP / Dynamic IP	SUPPORT
IP Server / DDNS	SUPPORT
Web Server	YES
Supported Protocol	HTTP, FTP, TCP/IP, DHCP, ARP, DNS, ICMP
Multi-access	Max. 50 users
Bit rate [Max]	5,000Kbps
Motion alarm and image transmission	FTP, SMTP(E-mail) / SMS (Korea)
VIDEO	
RESOLUTION	704X480[MAX] / 352X240
TV TYPE	NTSC / PAL
Frame Rate[Max]	30fps
COMPRESSION	MPEG-4 Dual Stream COMPRESSION RATIO: 200:1(Typical)
TEST VIDEO OUTPUT	Analogue composite video output
SYSTEM	
F/W UPGRADE	BY INTERNET
LANGUAGE	English / Japanese / Korean
CAMERA	Same spec as SK-P400X
POWER	DC 12V, 1.2A

PC Application [Viewer & Controller]

PC OS	Win2000/XP/NT
WEBVIEW	Built-in Web-view
MULTI-CHANNEL VIEWER	Multi-channel viewer, Record, Search, and etc.

