



FULL HD OVER COAX USE YOUR EXISTING COAX CABLE

# HDSDI

## WALL MOUNT PACK ACCESSORIES


- Manual
- Bracket Sealing Rubber Pad
- Video & Data Cable
- L Shape Star Wrench
- Mounting Parts



WALL MOUNT

**3 MEGA PIXEL**  
Up To 1080p

**x22** MORE COVERAGE than  
Conventional CCTV Camera



# 1080P IN/OUTDOOR PTZ WITH HIGH SPEED x360 ZOOM

**x30** OPTICAL ZOOM  
**x360** TOTAL ZOOM

CEILING MOUNT

## CEILING MOUNT PACK ACCESSORIES

- Manual
- Bracket Sealing Rubber Pad
- Video & Data Cable
- L Shape Star Wrench
- Mounting Parts



MADE IN KOREA



**FULL HD OVER COAX USE YOUR EXISTING COAX CABLE**

# HDSDI


**x30** OPTICAL ZOOM  
**x360** TOTAL ZOOM



## KEY FEATURES

- 3.0 Mega-Pixel Resolution PTZ
- x360 Zoom Control (Optical x30 / Digital x12)
- True Day & Night with ICR (IR Cut Filter)
- WDR (Wide Dynamic Range)
- NR (Noise Reduction) / Image Stabilization Function
- Minimum Illuminance (0.8 Lux @ Color / 0.1 Lux @ B/W)
- Super Speed (500°/SEC.) with 360° Endless Pan Rotation
- The Shortest Path with Vector Drive Technology
- Micro Control (0.05°/SEC.) with Micro Stepping Control Technology
- Super Video Quality with RAW Video Data
- HD-SDI Standard Support (HDcctvM V1.0 / 1.485Gb/s / SMPTE 292M)
- Simultaneous HD-SDI & Composite Output
- OSD(On-Screen Display) Menu with Password Function
- 8 Privacy Masks with Spherical Coordinates
- 8 Sets of Scheduler Function with Real Time Clock
- 255 Presets (46 Presets reserved for Hot Keys) 10 Swings / 4 Patterns / 8 Groups
- Frame Freeze Function
- Vandalproof / Weatherproof with Built-in Fan & Heater
- Waterproof (IP 67)

## DIMENSIONS



Camera	Image Sensor	6.49mm (1/2.8 Type) CMOS Sensor	
	Resolution	3M Pixels (2096 × 1561)	
	ISP	XDI-II	
	Zoom	Optical ×30 & Digital ×12	
	Focal Length	F1.6~5.0, f=4.3~129.0 mm	
	Gain Control	Auto / Low / Middle / High	
	Shutter Control	Auto / Manual (1/30 ~ 1/10,000 SEC.)	
	White Balance	Auto / ATW / One Push / Manual	
	Day & Night	Auto / Day / Night (ICR)	
	Minimum Illuminance	0.8 Lux (Color, AGC 30, Sens-up Off) / 0.1 Lux (B/W, AGC 30, Sens-up Off)	
	BLC	WDR / BLC / Off	
	Sens-up	Off / Auto (x2, x3, x4, ...x64)	
	NR (Noise Reduction)	3D-DNR (Off / Low / Middle / High)	
	Privacy Zone	8 Masks with Spherical Coordinate	
	Image Stabilization	On / Off	
Pan/Tilt	Range	Pan : 360° (Endless) / Tilt : 90°	
	Pan/Tilt Speed	Preset : 500° / SEC. Manual : 0.05° ~ 360° / SEC. (Zoom Proportional) Swing : 10° ~ 180° / SEC.	
	Preset	255 Presets (46 Presets reserved for Hot Keys)	
	Pattern	4 Patterns [768 Commands (Approximate 5 Minutes) / 1 Pattern]	
	Swing	10 Swings	
	Group	8 Groups (MAX. 40 Actions with The Combination of Preset, Pattern and Swing)	
	Scheduler Function	8 Scheduler Functions with RTC (Real Time Clock)	
	Other Functions	Auto Flip, Auto Parking, Power-up Action & etc.	
Video	Output	2 × BNC (HD-SDI and CVBS)	
	HD-SDI Standard	HDcctv V1.0 / 1.485Gb/s / SMPTE 292M Resolution : 1080p30, 1080i60, 720p60/30	
	CVBS	1.0 Vp-p	
RTC (Real Time Clock)	YES (RTC Battery Backup Time : Approximate 2 Weeks)		
OSD	YES (English)		
Serial Port	Port	RS-485 for PTZ Control	
	Protocol	Pelco-D, Pelco-P Selectable	
Sensor / Alarm	Sensor Input	3 Inputs, Photo-Coupler Type, DC 5V~12V	
	Alarm Output	1 Output, Relay Output, MAX. Load DC 24V / 1.0A or AC 125V / 0.5A	
Physical	Mount Bracket	Wall Mount Bracket or Ceiling Mount Bracket	
	Dimension	Dome	Ø150mm / Ø5.9"
		Wall Mount	200(Ø) × 408(H) [mm] / 7.87"(Ø) × 16.1"(H)
		Ceiling Mount	300 × 309(H) [mm] / 11.8" × 12.2"(H)
	Weight	Approximate	3.6 Kg / 7.9 Lbs with Wall Mount Bracket 3.4 Kg / 7.5 Lbs with Ceiling Mount Bracket
		Material	Dome : Poly Carbonate / Housing : Aluminum
	Rated Power	Dual Power Support : DC 12V / 1.8A or AC 24V / 2.0A	
	Waterproof	IP 67	
	Fan	Always ON	
	Heater	Operation Start from Internal Temperature 10 °C (50 °F)	
	Operating Temp.	-30 °C ~ 50 °C (-34 °F ~ 122 °F)	

MADE IN KOREA